

Commercial TV AN960H Series

Commercial Lite

Voice

Recognition

Pro:Centric Value Pro:Centric Direct

Pro:Centric Smart

4K UHD OLED Hotel Smart TV with

Pro:Centric Hotel Management Solutions





Pro:Centric Solutions



AN960H Series				
Design	Stand Type	2 pole		
	Inch	77" / 65" / 55"		
Display	Resolution	3,840 × 2,160 (UHD)		
	Туре	OLED		
Broadcasting	Digital	ATSC / Clear QAM		
System	Analog	NTSC		
Solution	Pro:Centric (Smart, Cloud, Direct, V), Quick Menu			




LG OLED Self-emissive

LG Hospitality TV is unique thanks to its self-lit technology. Millions of OLED pixels come together to deliver the next level of TV. Enjoy the deep black, the rich colors and the vivid picture quality.



Pro:Centric Cloud

Pro:Centric Cloud improves the usability of enterprise's CMS solution and cloudification of system, reinforcing the service of 3rd party solution. It also offers various design templates, improving data collection and analytics platform with an eye-catching dashboard.



Pro:Centric Direct*

The hotel content management solution Pro:Centric Direct offers easy and simple editing tools, making it easy to perform service and IP network-based remote management with a single click. The Pro:Centric Direct solution enables users to edit their interface easily by providing customized interface and efficiently manages all TVs in the room. The latest PCD version provides IoT-based in-room control as well as voice control function through LG Natural Language Processing (NLP). These IoT and voice-related functions will be your starting point to prepare for the hotel rooms of next generation through artificial intelligence. Note that some features may not be supporting depending on the version of Pro:Centric Direct.



More Innovative LG webOS22

Explore the latest webOS22 of LG Smart TV features, and discover TVs that deliver innovative technology and remarkable clarity with vivid colors. Newly added Always on Display and Game Optimizer functions allow you to enter the new visual excitement.



Always On Display

Black monster TV turns into live screens with clock, art pieces or even display your own images.



Game Optimizer

LG Game Optimizer will get you and keep you in the action through selection of game mode, picture adjustment, etc.



SoftAP

Software-enabled Access Point* (SoftAP) is a "virtual" Wi-Fi feature that uses TV as a wireless hotspot, enabling guests to connect their own devices to the SoftAP.

* SoftAP should be set in the installation menu after the TV is turned on, and Screen Share may not be operated at the same time.




Pro:Idiom

Digital Rights Management (DRM) technology provides access to premium content to help assure rapid and broad deployment of HDTV and other high-value digital content.

CONNECTIVITY

77" / 65" / 55"

Rear



Side

ANTENNA/	HDN	AI IN	USB IN 🚓
CARLEIN	2 (eARC/ARC)	3	1

* Jack Panels may differ from the above image, so please contact LG sales team to verify before ordering.

SPECIFICATIONS

		77AN960H0UD	65AN960H0UD	55AN960H0UD	
Category	Category	Pro:Centric Smart	Pro:Centric Smart	Pro:Centric Smart	
Design	Stand Type	Base-mounted Dual	Base-mounted Dual	Base-mounted Dual	
DCSIgIT	Front Color	OLED (4 Side Cinema Screen)	OLED (4 Side Cinema Screen)	OLED (4 Side Cinema Screen)	
Display –	Inch	77"	65"	55"	
	Resolution	3,840 × 2,160 (UHD)	3,840 × 2,160 (UHD)	3,840 × 2,160 (UHD)	
Video	HDR 10 Pro / HDR HLG	Yes / Yes	Yes / Yes	Yes / Yes	
VIGCO	Game Optimizer	Yes	Yes	Yes	
Audio - Broadcasting -	Speaker (Sound Output)	10 W + 10 W	10 W + 10 W	10 W + 10 W	
	Speaker System	2.0 ch	2.0 ch	2.0 ch	
	AI Acoustic Tuning	Yes (Ready)	Yes (Ready)	Yes (Ready)	
	LG Sound Sync	Optical/Bluetooth wireless	Optical/Bluetooth wireless	Optical/Bluetooth wireless	
	Digital (Terrestrial / Cable / Satellite)	ATSC, Clear QAM, Analog NTSC	ATSC, Clear QAM, Analog NTSC	ATSC, Clear QAM, Analog NTSC	
	Global IPTV Support	Yes	Yes	Yes	
Hospitality Solution	Solution Type	Pro:Centric (Smart, Cloud, Direct, V) Quick Menu 5.0	Pro:Centric (Smart, Cloud, Direct, V) Quick Menu 5.0	Pro:Centric (Smart, Cloud, Direct, V) Quick Menu 5.	
	DRM	Pro:ldiom (Mobile Lite)	Pro:Idiom (Mobile Lite)	Pro:Idiom (Mobile Lite)	
Smart Features		'eb Browser, Pre-loaded App, SDP Server Co ARC (HDMI 2), Voice Recognition (Standalo			
		ARC (HDMI 2), Voice Recognition (Standalo			
Features Hospitality		ARC (HDMI 2), Voice Recognition (Standalo	ne / Solution), Wake on RF, Diagnostics (IP		
Features Hospitality	LG ThinQ App Compatibility, HDMI-	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line C	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), n HDMI 2.0 In,	
Features Hospitality Features	LG ThinQ App Compatibility, HDMI-	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line C	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm Put (3.5 mm Stereo Jack, 400 mV RMS), MP	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), n HDMI 2.0 ln,	
Features Hospitality Features	LG ThinQ App Compatibility, HDMI-	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line O Service	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm Dut (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), ıl, HDMI 2.0 ln, t, Aux) x2	
Features Hospitality Features	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line O Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm tut (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 × 32.8 × 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), P, HDMI 2.0 in, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg	
Features Hospitality Features	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D)	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line O Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm ut (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 x 32.8 x 1.8 in. 1,449 × 832 × 45.9 mm	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), n HDMI 2.0 in, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm	
Features Hospitality Features	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line C Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 x 41.6 x 38.9 in. 1,719 × 1,057 × 989 mm	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm but (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 x 32.8 x 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 x 35.3 x 9.3 in. 1,449 × 896 × 235 mm	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), 1, HDMI 2.0 ln, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 x 30.4 x 903 in. 1,228 × 772 × 235 mm	
Features Hospitality Features Connectivity	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight Dimensions with Stand (W × H × D)	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line O Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 x 41.6 x 38.9 in.	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm tut (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 × 32.8 × 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 × 35.3 × 9.3 in.	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), l, HDMI 2.0 ln, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 x 30.4 x 903 in.	
Features Hospitality Features Connectivity	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight Dimensions with Stand (W × H × D) Weight with Stand	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line C Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 x 41.6 x 38.9 in. 1,719 × 1,057 × 989 mm 46.3 lbs. / 21 kg 72.4 x 44.5 x 7.9 in.	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm but (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 x 32.8 x 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 x 35.3 x 9.3 in. 1,449 × 896 × 235 mm 38.1 lbs. / 17.3 kg 63.0 x 37.4 x 6.8 in.	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), H, HDMI 2.0 In, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 x 30.4 x 903 in. 1,228 × 772 × 235 mm 32.0 lbs. / 14.5 kg 53.5 x 31.9 x 6.8 in.	
Features Hospitality Features Connectivity	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight Dimensions with Stand (W × H × D) Weight with Stand Shipping Dimensions (W × H × D)	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line O Service 300 × 200 mm 67.7 × 32.8 × 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 × 41.6 × 38.9 in. 1,719 × 1,057 × 989 mm 46.3 lbs. / 21 kg 72.4 × 44.5 × 7.9 in. 1,839 × 1,130 × 200 mm	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm but (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 × 32.8 × 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 × 35.3 × 9.3 in. 1,449 × 896 × 235 mm 38.1 lbs. / 17.3 kg 63.0 × 37.4 × 6.8 in. 1,600 × 950 × 172 mm	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), N, HDMI 2.0 In, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 x 30.4 x 903 in. 1,228 × 772 × 235 mm 32.0 lbs. / 14.5 kg 53.5 x 31.9 x 6.8 in. 1,360 × 810 × 172 mm	
Features Hospitality Features Connectivity Mechanical	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight Dimensions with Stand (W × H × D) Weight with Stand Shipping Dimensions (W × H × D) On Bezel Width (L/R/T/B)	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), C Audio Line O Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 x 41.6 x 38.9 in. 1,719 × 1,057 × 989 mm 46.3 lbs. / 21 kg 72.4 x 44.5 x 7.9 in. 1,839 × 1,130 × 200 mm 11 / 11 / 12.4 / 16.7 mm	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm 1ut (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 × 32.8 × 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 × 35.3 × 9.3 in. 1,449 × 896 × 235 mm 38.1 lbs. / 17.3 kg 63.0 × 37.4 × 6.8 in. 1,600 × 950 × 172 mm 10.1 / 10.1 / 9.9 / 12.8 mm	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), n HDMI 2.0 ln, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 x 30.4 x 903 in. 1,228 × 772 × 235 mm 32.0 lbs. / 14.5 kg 53.5 x 31.9 x 6.8 in. 1,360 × 810 × 172 mm 9.1 / 9.1 / 8.9 / 12.8 mm	
Features Hospitality Features Connectivity	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight Dimensions with Stand (W × H × D) Weight with Stand Shipping Dimensions (W × H × D) On Bezel Width (L/R/T/B) Off Bezel Width (L/R/T/B)	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line C Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 x 41.6 x 38.9 in. 1,719 × 1,057 × 989 mm 46.3 lbs. / 21 kg 72.4 x 44.5 x 7.9 in. 1,839 × 1,130 × 200 mm 11/11/12.4/16.7 mm 1.3/1.3/1.3/16.7 mm	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm but (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 x 32.8 x 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 x 35.3 x 9.3 in. 1,449 × 896 × 235 mm 38.1 lbs. / 17.3 kg 63.0 x 37.4 x 6.8 in. 1,600 × 950 × 172 mm 10.1 / 10.1 / 9.9 / 12.8 mm 3.2 / 3.2 / 3.2 / 3.2 mm	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), H, HDMI 2.0 In, t, Aux) x2 300 × 200 mm 48.3 × 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 × 30.4 × 903 in. 1,228 × 772 × 235 mm 32.0 lbs. / 14.5 kg 53.5 × 31.9 x 6.8 in. 1,360 × 810 × 172 mm 9.1 / 9.1 / 8.9 / 12.8 mm 3.2 / 3.2 / 3.2 / 3.2 mm	
Features Hospitality Features Connectivity Mechanical Electrical	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight Dimensions with Stand (W × H × D) Weight with Stand Shipping Dimensions (W × H × D) On Bezel Width (L/R/T/B) Off Bezel Width (L/R/T/B) Power Supply (Voltage, Hz)	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line O Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 x 41.6 x 38.9 in. 1,719 × 1,057 × 989 mm 46.3 lbs. / 21 kg 72.4 x 44.5 x 7.9 in. 1,839 × 1,130 × 200 mm 11/11/12.4/16.7 mm 1.3/1.3/1.3/16.7 mm 100-240 Vac, 50/60 Hz	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm but (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 × 32.8 × 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 × 35.3 × 9.3 in. 1,449 × 896 × 235 mm 38.1 lbs. / 17.3 kg 63.0 × 37.4 × 6.8 in. 1,600 × 950 × 172 mm 10.1 / 10.1 / 9.9 / 12.8 mm 3.2 / 3.2 / 3.2 / 3.2 mm	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), N, HDMI 2.0 In, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 x 30.4 x 903 in. 1,228 × 772 × 235 mm 32.0 lbs. / 14.5 kg 53.5 x 31.9 x 6.8 in. 1,360 × 810 × 172 mm 9.1 / 9.1 / 8.9 / 12.8 mm 3.2 / 3.2 / 3.2 / 3.2 mm 100-240 Vac, 50/60 Hz	
Features Hospitality Features Connectivity Mechanical	LG ThinQ App Compatibility, HDMI- Set Side Set Rear VESA Compatible Dimensions (W × H × D) Weight Dimensions with Stand (W × H × D) Weight with Stand Shipping Dimensions (W × H × D) On Bezel Width (L/R/T/B) Off Bezel Width (L/R/T/B) Power Supply (Voltage, Hz) Power Consumption (Typ. / Max.)	ARC (HDMI 2), Voice Recognition (Standalo Port Block, Instant ON, V-LAN ID, Auto USB (2.0), D Audio Line C Service 300 × 200 mm 67.7 x 32.8 x 1.8 in. 1,719 × 832 × 45.9 mm 45.0 lbs. / 20.4 kg 67.7 x 41.6 x 38.9 in. 1,719 × 1,057 × 989 mm 46.3 lbs. / 21 kg 72.4 x 44.5 x 7.9 in. 1,839 × 1,130 × 200 mm 11 / 11 / 12.4 / 16.7 mm 1.3 / 1.3 / 1.3 / 16.7 mm 100-240 Vac, 50/60 Hz 352 W / 378 W	ne / Solution), Wake on RF, Diagnostics (IP Off / Sleep Timer, Energy Saving Mode RF In (Tuner), HDMI 2.0 In (x2), USB 2.0 Digital Audio Out (Optical), RS-232C (3.5 mm Ponty (3.5 mm Stereo Jack, 400 mV RMS), MP Only (3.5 mm Stereo Jack), RJ45 (Ethernet 300 × 200 mm 57.0 × 32.8 × 1.8 in. 1,449 × 832 × 45.9 mm 37.7 lbs. / 17.1 kg 57.0 × 35.3 × 9.3 in. 1,449 × 896 × 235 mm 38.1 lbs. / 17.3 kg 63.0 × 37.4 × 6.8 in. 1,600 × 950 × 172 mm 10.1 / 10.1 / 9.9 / 12.8 mm 3.2 / 3.2 / 3.2 / 3.2 mm 100-240 Vac, 50/60 Hz 260 W / 283 W	Remote), Simplink (HDMI-CEC) (1.4) n TRRS Jack), l, HDMI 2.0 ln, t, Aux) x2 300 × 200 mm 48.3 x 27.9 x 1.8 in. 1,228 × 708 × 45.9 mm 31.5 lbs. / 14.3 kg 48.3 x 30.4 x 903 in. 1,228 × 772 × 235 mm 32.0 lbs. / 14.5 kg 53.5 x 31.9 x 6.8 in. 1,360 × 810 × 172 mm 9.1 / 9.1 / 8.9 / 12.8 mm 3.2 / 3.2 / 3.2 / 3.2 mm 100-240 Vac, 50/60 Hz 210 W / 238 W	

* Specifications are subject to change without notice. Please make sure to check the product manual for details about product usage.

CONTACT US :

Tel: 1-877-777-9769

www. lghospitality.com

Sales@LGHospitality.com